

EL1150

Small Case



- **Watertight, crushproof, and dustproof**
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Stainless steel hardware
- Pick N Pluck™ with convoluted lid foam
- [Lifetime Guarantee of Excellence](#)

CONFIGURATIONS

EL1150 - Standard

EL1150NF - With No Foam

DIMENSIONS

Interior (L x W x D): 8.29 x 5.79" x 3.75 (21.1 x 14.7 x 9.5 cm)

Exterior (L x W x D): 9.44 x 7.80" x 4.29 (24 x 19.8 x 10.9 cm)

Lid Depth: 0.75"

Bottom Depth: 2.87"

Total Depth: 3.62"

Int Volume: 0.1 ft³

MATERIALS

Body: Polypropylene

Latch: Polypropylene

O-Ring: Polymer

Pins: Stainless Steel

Foam: 1.3 lb Polyurethane

Purge Body: ABS

Purge Vent: 3 Micron Hydrophobic Non-Woven

Purge O-Ring: 70 Shore Nitrile

COLORS



Black

Silver

Orange

Yellow

Blue

OD Green

Desert Tan

WEIGHT

Weight With Foam: 1.75 lbs
Weight Without Foam: 1.61 lbs
Buoyancy: 8.00 lbs
Master Pack Weight: 13.95 lbs

TEMPERATURE

Minimum Temperature: -40°
Maximum Temperature: 210°

CERTIFICATIONS

IP67
Def Stan 81-41
STANAG 4280

FOAM PROPERTIES

Layer 1 (Lid): 0.74" Convolute
Layer 2 (Base): 0.50" Pad
Layer 3 (Base): 2.53" Pick N Pluck

OTHER

Master Pack: 6
Military: yes